

Declaration of compliance

Regarding following items: 31741 - Broom, 420 mm, Pink
31791 - Broom, 435 mm, Pink
70471 - High-Low Brush, 260 mm, Pink
70601 - Wall-/Floor Washing Brush, 300 mm, Pink

Producer: **Vikan A/S**
Rævevej 1
7800 Skive
Denmark
Tel.: +45 96 14 26 00

Materials: **Polypropylene 97 %, pink masterbatch 2 % and foamer 1% in the brush block.**

Polypropylene:

Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No. 10/2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011, 1282/2011, 1183/2012 and 202/2014 are included.

This polypropylene grade contains the following dual use additives: Glycerol monostearat, calcium stearat and talc.

No monomers and additives with specific migration limit (SML) are used.

Pink masterbatch and foamer:

Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No. 10/2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011, 1282/2011, 1183/2012 and 202/2014 are included.

Following monomers and additives with specific migration limit (SML) are used in the pink masterbatch:
Ref no. 13380/25600/94960, cas no. 77-99-6, 1,1,1-trimethylolpropane; ref no. 68320, cas no. 2082-79-3, octadecyl-3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionat and ref no. 39090, N,N-bis(2-hydroxyethyl)alkyl(c 8 - C 18) amine.
The product meets the requirement regarding SML either by calculations or product testing (ref. no 39090).

Dual use additives: Glycerol monostearate, calcium stearate and talc.

Regarding the foamer following additives with specific migration limit (SML) are used: Vinyl acetat, Cas no. 108-05-4 with SML 12.00 mg/kg and 2,6-Di-tert-Butyl-p-cresol (BHT), Cas no. 128-37-0 with SML 3.00 mg/kg.
The product meets the requirement regarding SML for both materials either by product testing (Vinyl acetate) or by calculation (BHT).

Filaments made from polybutyleneterephthalate (PBT)

Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No. 10/2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011, 1282/2011, 1183/2012 and 202/2014 are included.

This filament grade contains the following "dual use" additives: Phosphoric acid.

Monomers and additives with specific migration limit (SML) are used. It is to be determined at the moment.

Stainless steel thread

No restrictions or specific migration levels.

FDA:	All raw materials in this product are in compliance with FDA (Food and Drug Administration in the USA) CFR 21.
EU Commission:	In accordance with EU Commission Regulation no. 1935/2004 the product is intended for food contact. The products can be marked with the "glass & fork" symbol on the packaging or by labeling. The product is produced according to EU Commission Regulation no. 2023/2006 on good manufacturing practices for materials and articles intended to come into contact with food (GMP). Overall migration tests are made on similar products. The products meet the requirements regarding overall migration to 50 % ethanol, 3 % acetic acid, tenax (for non liquid foodstuff) and isooctane (substitute to olive oil).
Food contact:	No limitation
Usage temperature:	Min. temp.: -20 °C Max. temp.: 80 °C
General:	It is recommended that equipment is cleaned, disinfected and sterilised, as appropriate to it's intended use, before use. It is also important to clean, disinfect and sterilise equipment after use, using the appropriate decontamination chemicals, concentrations, times and temperatures. Appropriate equipment decontamination will minimise risk of microbial growth and cross contamination and maximise the efficiency and durability of the equipment. Max. Wash temp.: 121 °C
Date:	21st november 2014 
Made by:	Bettina Amdisen-Christensen Laboratory and Environmental Coordinator