



Declaration of compliance

Regarding following items: 31665 - Broom w/ Straight Neck, 310 mm, White
31745 - Broom, 420 mm, White
31945 - Broom, 600 mm, White
44015 - Detail Brush, 220 mm, White
70475 - High-Low Brush, 260 mm, White
70605 - Wall-/Floor Washing Brush, Stiff, 300 mm, White
70615 - Wall-/Floor Washing Brush, Medium, 300 mm, White
70625 - Wall-/Floor Washing Brush, 470 mm, White
70685 - Broom, 300 mm, White

Producer: **Vikan A/S**
Rævevej 1
7800 Skive
Denmark
Tel.: +45 96 14 26 00

Materials: **Polypropylene 97 %, white masterbatch 2 % and foamer 1% in the brush block.**

Polypropylene:

Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No. 10/2011 of 14. January 2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011 (1. April 2011), 1282/2011 (10. December 2011) and 1183/2012 (30. November 2012) are included.

This polypropylene grade contains the following "dual use" additives: Glycerol monostearat, calcium stearat and talc.

No monomers and additives with specific migration limit (SML) are used.

White masterbatch and foamer:

Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No. 10/2011 of 14. January 2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011 (1. April 2011), 1282/2011 (10. December 2011) and 1183/2012 (30. November 2012) are included.

White masterbatch contains the following "dual use" additive: TiO₂.

Monomers and additives with specific migration limit (SML) in the white masterbatch are used. It is to be determined at the moment.

Regarding the foamer following additives with specific migration limit (SML) are used: Vinyl acetat, Cas no. 108-05-4 with SML 12.00 mg/kg and 2,6-Di-tert-Butyl-p-cresol (BHT), Cas no. 128-37-0 with SML 3.00 mg/kg. The product meets the requirement regarding SML for both materials either by product test (Vinyl acetate) or by calculation (BHT).

Further informations can be given on request.

Filaments made from polybutyleneterephthalate (PBT)

Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No. 10/2011 of 14. January 2011 on plastic materials and articles intended to come into contact with foodstuffs with current amendments included.

This filament grade contains the following "dual use" additives: Phosphoric acid.

Monomers and additives with specific migration limit (SML) are used. It is to be determined at the moment.

Stainless steel thread

No restrictions or specific migration levels.

FDA: All raw materials in this product are in compliance with FDA (Food and Drug Administration in the USA) CFR 21.

EU Commission: In accordance with EU Commission Regulation no. 1935/2004 of October 2004 the product is intended for food contact. The handle can be marked with the "glass & fork" symbol on the packaging or by labeling.

The product is produced according to EU Commission Regulation no. 2023/2006 of 22. December 2006 on good manufacturing practices for materials and articles intended to come into contact with food (GMP).

Overall migration tests are made on similar products. The products meet the requirements regarding overall migration to 50 % ethanol, 3 % acetic acid, tenax (for non liquid foodstuff) and isooctane (substitute to olive oil).

Food contact: No limitation

Usage temperature: Min. temp.: -20 °C
Max. temp.: 80 °C

General: It is recommended that equipment is cleaned, disinfected and sterilised, as appropriate to its intended use, before use.
It is also important to clean, disinfect and sterilise equipment after use, using the appropriate decontamination chemicals, concentrations, times and temperatures.
Appropriate equipment decontamination will minimise risk of microbial growth and cross contamination and maximise the efficiency and durability of the equipment.

Max. Wash temp.: 121 °C

Date: 26th January 2014

Made by: Inger Arensbach
Quality- and environmental manager